



IPX-ED-24V

IPX-ED-POE

ENVIRONMENTAL DOME ENCLOSURES

IPX-ED-24V
IPX-ED-POE

These high-quality, environmental enclosures are engineered to protect network pan/tilt video cameras from physical and environmental damage. Available in either 24VAC or Power-over-Ethernet versions, the IPX-CE-24V and IPX-CE-POE are compatible with leading brands of compact IP-based pan/tilt video surveillance cameras. Durable, insulated design facilitates the installation of cameras outdoors while maintaining ideal operating temperature with a thermostatically-controlled heater and fan. Heavy-duty mounting bracket conceals all cabling and can be installed on any vertical surface. Optional pole and corner mount adapters also available.

SPECIFICATIONS

Construction

- Die-Cast Aluminum Body
- Clear Acrylic Lower Dome

Power Requirement

- 24VAC Input
- Power-over-Ethernet 802.3at
- Built-in 12VDC 2A Output Terminals

Environmental Rating

- IP66 Certified

Operating Temperature

- -30°C to 50°C (-22° to 122° F)
- 0 to 95% Relative Humidity

Color

- Beige

Heater

- Activates at 0°C (32°F)
- Di-Activates at 10°C (50°F)

Internal Fan

- Activates at 40°C (104°F)
- Di-Activates at 25°C (77°F)

Measurements

- Length13.8 inches
- Width 8.6 inches
- Height12.4 inches
- Weight 7.6 lbs.

Optional Accesories

- Pole Mount Adapter
- Corner Mount Adapter
- 24VAC Plug-in Transformer

Supported Cameras

- Axis 213 PTZ
- Canon VB-C50iR
- D-Link DCS-5300
- D-Link DCS-6620
- Toshiba IK-WB21A
- Toshiba IK-WB16A/W
- Vivotek PZ8111/W
- Vivotek PZ7131/32
- Vivotek PT7135/37

Product specifications and availability subject to change without notice.

Dealer Inquiries:

IPX International, Inc.

1775 Highway 34, Suite D-11, Farmingdale, NJ 07727

Tel: (866) 323-9647 E-mail: sales@ipxinc.com